



ENGINEERING & TECHNICAL DATA — Flex-Tube® TR-FR

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
3	.45	.035	4	2:1	22	15
4	.6	.035	5	2:1	20	12
5	.8	.035	6	2:1	18	11
6	1	.035	7	2:1	16	10
7	1.3	.035	8	2:1	13	9
8	1.7	.035	9.75	2:1	12	8
10	2.1	.040	11	2:1	6	7

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Medium weight coextruded thermoplastic rubber hose with a rigid external polypropylene helix

Temperature Range: -60°F to 275°F

Standard Color: Black with Black Helix (Custom Colors Available)

Standard Lengths: 25 Feet

- Manufactured with materials compliant with UL 94-V0

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY